# DECLARATION OF PERFORMANCE (DOP)

	NO. 90065600-CPR-20150529	
1.	Product Type:	Freestanding stove Scan 65
2.	Type, batch or serial number:	Scan 65 series (Scan 65-1, Scan 65-3, Scan 65-5, Scan 65-7, Scan 65-9)
3.	Intended use of the product:	Heat distribution/room heating Without hot water supply Fuel type: Wood
4.	Name and Address of the manufacturer:	Scan A/S Glassvænget 3-9 5492 Vissenbjerg
5.	Contact address:	No relevance
6.	AVCP System(s) of assessment and verification of constancy op performance (AVCP) of the construction product as set out in CPR, Annex V	System 3
7.	Notified body:  Test report no:	RWE NB-No 1427 FSPS-Wa 2308 EN
8.	Declared performance	
	Harmonized technical specification	EN 13240:2001/A2:2004/AC:2007
	Essential characteristics	Performance
	Fire safety Reaction to fire Distance to combustible materials Risk of burning fuel falling out	A1 Minimum distances in mm: Rear: 150 Sides: 350 Front: 1000 NPD
	Emission of combustion products	CO [0,078 %] NOx [104 mg/Nm³] OGC [81 mg/Nm³] Dust [20 mg/Nm³]
	Surface temperature	Pass
	Electrical safety	-
	Cleanability	Pass
	Maximum water operating pressure	-
	Flue gas temperature at nominal heat output [EN]	T [245°C]
	Mechanical resistance (to carry a chimney/flue)	NPD
	Thermal output Normal heat output Room heating output Water heating output	6 kW
	Energy efficiency	ŋ [82 %]

## **DECLARATION:**

The performance of the product identified in points 1 and 2 in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

### Signed on behalf of the manufacturer:

Morten Bach (R&D LAB)

Vissenbjerg, 27.08.2015





# DECLARATION OF PERFORMANCE (DOP)

	NO. 90065601-CPR-20150529	
1.	Product Type:	Freestanding stove Scan 65
2.	Type, batch or serial number:	Scan 65 series (Scan 65-2, Scan 65-4, Scan 65-6, Scan 65-8, Scan 65-10)
3.	Intended use of the product:	Heat distribution/room heating Without hot water supply Fuel type: Wood
4.	Name and Address of the manufacturer:	Scan A/S Glassvænget 3-9 5492 Vissenbjerg
5.	Contact address:	No relevance
6.	AVCP System(s) of assessment and verification of constancy op performance (AVCP) of the construction product as set out in CPR, Annex V	System 3
7.	Notified body:  Test report no:	RWE NB-No 1427 FSPS-Wa 2308 EN
8.	Declared performance	
	Harmonized technical specification	EN 13240:2001/A2:2004/AC:2007
	Essential characteristics	Performance
	Fire safety Reaction to fire Distance to combustible materials Risk of burning fuel falling out	A1 Minimum distances in mm: Rear: 150 Sides: 500 Front: 1000 NPD
	Emission of combustion products	CO [0,098 %] NOx [117 mg/Nm³] OGC [92 mg/Nm³] Dust [20 mg/Nm³]
	Surface temperature	Pass
	Electrical safety	-
	Cleanability	Pass
	Maximum water operating pressure	-
	Flue gas temperature at nominal heat output [EN]	T [264°C]
	Mechanical resistance (to carry a chimney/flue)	NPD
	Thermal output Normal heat output Room heating output Water heating output	6 kW
	Energy efficiency	ŋ [79 %]

## **DECLARATION:**

The performance of the product identified in points 1 and 2 in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

### Signed on behalf of the manufacturer:

Morten Bach (R&D LAB)

Vissenbjerg, 27.08.2015



